








Const. 8x26-8x31-8x36-8x41-8x49 WS
Min. & Max. Dia 10 mm - 150 mm
Core FC & IWRC
Coating UNGALVANIZED & GALVANIZED
Other Request Contact US

1770

1960

2160

Cons.	Min. Dia (MM)	Max. Dia (MM)	Min. Dia (MM)	Max. Dia (MM)	Min. Dia (MM)	Max. Dia (MM)
8 x 26	10	110	10	90	10	70
8 x 31	10	120	10	100	10	80
8 x 36	10	130	10	110	10	90
8 x 41	32	150	32	120	32	100
8 x 49	32	150	32	120	32	100



Rope Dia. (mm)	Dia. Tolerance (%)	Unit Weight (kg/m)	Minimum Breaking Load (kN) [Acc to Wire Tensile Strength]		
			1770 [N/mm ²]	1960 [N/mm ²]	2160 [N/mm ²]
10		0.340	52	57	63
11		0.411	63	69	77
12		0.490	75	83	91
13		0.575	88	97	107
14		0.666	102	113	124
15		0.765	117	129	142
16		0.870	133	147	162
17		0.983	150	166	183
18		1.102	168	186	205
19		1.227	187	207	228
20		1.360	207	230	253
21	+5 0	1.499	229	253	279
22		1.646	251	278	306
24		1.958	299	331	365
26		2.298	351	388	428
28		2.666	407	450	496
30		3.060	467	517	570
32		3.482	531	588	648
34		3.930	600	664	732
36		4.406	672	744	820
38		4.910	749	829	914
40	5.440	830	919	1013	
42	5.998	915	1013	1116	
44	6.582	1004	1112	1225	
48	7.834	1195	1323	1458	
52	9.194	1402	1553	1711	
56	10.662	1626	1801	1985	
60	12.240	1867	2067	2278	

Rope Dia. (mm)	Dia. Tolerance (%)	Unit Weight (kg/m)	Minimum Breaking Load (kN) [Acc to Wire Tensile Strength]		
			1770 [N/mm ²]	1960 [N/mm ²]	2160 [N/mm ²]
10		0.407	63	70	77
11		0.492	76	84	93
12		0.586	91	100	111
13		0.688	106	118	130
14		0.798	124	137	151
15		0.916	142	157	173
16		1.042	161	179	197
17		1.176	182	202	222
18		1.319	204	226	249
19		1.469	227	252	278
20		1.628	252	279	308
21	+5 0	1.795	278	308	339
22		1.970	305	338	372
24		2.344	363	402	443
26		2.751	426	472	520
28		3.191	494	547	603
30		3.663	567	628	692
32		4.168	645	715	787
34		4.705	728	807	889
36		5.275	817	904	997
38		5.877	910	1008	1110
40	6.512	1008	1116	1230	
42	7.179	1112	1231	1356	
44	7.880	1220	1351	1489	
48	9.377	1452	1608	1772	
52	11.005	1704	1887	2079	
56	12.764	1976	2188	2411	
60	14.652	2268	2512	2768	